

AMENDMENTS TO THE SPECIFICATION:

Please amend the paragraph on page 8, beginning at line 31 as follows:

--Referring next to Figures 3 to 10, in an alternative embodiment of the invention the attachment device engaging portion ~~includes~~ is in the form of a pin or dowel 30 which is separable from the holder, generally referenced 31. The pin or dowel 30 includes a shaft 7 on which one or more projections 6 are provided. The holder 31 as shown in Figures 3 to 10 preferably includes one or more resilient fingers 26 which facilitate location and retention of a container with the holder. The attachment device engaging portion is an attachment device connector for attaching to a section 1.--

Please amend the paragraph on page 9, beginning at line 10 as follows:

--In a preferred embodiment the pin or dowel 30 may be rotated within the slot 5 until depressions 28 in the projections 6 engage with one or both projecting ribs 33 on an internal surface of the bracket adjacent to the slot 5. This prevents accidental rotation of the pin 30 when the holder 31 is moved relative to the bracket. In this configuration the holder 31 may be rotatable through a full 360° range of rotation relative to the bracket 40, without the projections 6 aligning with the slot 5 such that the pin 30 can disengage from the bracket 40. This may be particularly convenient when the tubular or rectilinear

section (not shown) to which the apparatus is to be engaged is close to vertical in orientation. Thus, the slot 5 and the surrounding region is a holder connector for the attachment device engaging portion.--